

unattended-upgrades

Un paquet est volontairement créé pour cette fonction de mise à jour automatique des paquets : unattended-upgrades

```
apt install unattended-upgrades apt-listchanges
```

Ajouter la notification mail à chaque upgrade en décommentant la ligne suivante dans le fichier /etc/apt/apt.conf.d/50unattended-upgrades

```
Unattended-Upgrade::Mail "<destination_mail_fqdn>";
```

```
/etc/apt/apt.conf.d/20auto-upgrades
```

```
APT::Periodic::Update-Package-Lists "1";  
APT::Periodic::Unattended-Upgrade "1";
```

Le fichier /etc/apt/apt.conf.d/50unattended-upgrades est présent. La partie suivante précise ce qu'on souhaite upgrader automatiquement. Le minimum à décocher sont les mises à jour de sécurité.

```
// Unattended-Upgrade::Origins-Pattern controls which packages are  
// upgraded.  
//  
// Lines below have the format format is "keyword=value,...". A  
// package will be upgraded only if the values in its metadata match  
// all the supplied keywords in a line. (In other words, omitted  
// keywords are wild cards.) The keywords originate from the Release  
// file, but several aliases are accepted. The accepted keywords are:  
// a,archive,suite (eg, "stable")  
// c,component (eg, "main", "contrib", "non-free")  
// l,label (eg, "Debian", "Debian-Security")  
// o,origin (eg, "Debian", "Unofficial Multimedia Packages")  
// n,codename (eg, "jessie", "jessie-updates")  
// site (eg, "http.debian.net")  
// The available values on the system are printed by the command  
// "apt-cache policy", and can be debugged by running  
// "unattended-upgrades -d" and looking at the log file.  
//  
// Within lines unattended-upgrades allows 2 macros whose values are  
// derived from /etc/debian_version:  
// ${distro_id} Installed origin.  
// ${distro_codename} Installed codename (eg, "jessie")  
Unattended-Upgrade::Origins-Pattern {  
    // Codename based matching:  
    // This will follow the migration of a release through different  
    // archives (e.g. from testing to stable and later oldstable).  
    // "o=Debian,n=jessie";  
    // "o=Debian,n=jessie-updates";
```

```
//      "o=Debian,n=jessie-proposed-updates";
//      "o=Debian,n=jessie,l=Debian-Security";

      // Archive or Suite based matching:
      // Note that this will silently match a different release after
      // migration to the specified archive (e.g. testing becomes the
      // new stable).
//      "o=Debian,a=stable";
//      "o=Debian,a=stable-updates";
//      "o=Debian,a=proposed-updates";
      "origin=Debian,codename=${distro_codename},label=Debian-Security";
};

Unattended-Upgrade::Mail "<fqdn_receiver>";
```

/etc/apt/listchanges.conf

```
[apt]
frontend=pager
email_address=root
confirm=0
save_seen=/var/lib/apt/listchanges.db
which=both
```

Exécuter la commande de mise à jour manuellement.

```
unattended-upgrade -d
```

From:
<https://wiki.ouieuhtoutca.eu/> - **kilsufi de noter**

Permanent link:
<https://wiki.ouieuhtoutca.eu/unattended-upgrades>

Last update: **2021/01/21 21:42**

